

# Canadian Bioinformatics Workshops

[www.bioinformatics.ca](http://www.bioinformatics.ca)

[bioinformaticsdotca.github.io](https://bioinformaticsdotca.github.io)

Supported by



This page is available in the following languages:

Afrikaans Ελληνικά Català Dansk Deutsch Ελληνικά English English (CA) English (GB) English (US) Esperanto  
 Castellano Castellano (AR) Español (CL) Castellano (CO) Español (Ecuador) Castellano (MX) Castellano (PE)  
 Euskara Suomi français français (CA) Galego עברית hrvatski Magyar Italiano 日本語 한국어 Macedonian Melayu  
 Nederlands Norsk Sesotho sa Leboa polski Português română slovenski jezik срpski (latinica) Sotho svenska  
 中文 華語 (台灣) isiZulu



## Attribution-Share Alike 2.5 Canada

### You are free:



to **Share** — to copy, distribute and transmit the work



to **Remix** — to adapt the work



### Under the following conditions:



**Attribution.** You must attribute the work in the manner specified by the author or licensor (but not in any way that suggests that they endorse you or your use of the work).



**Share Alike.** If you alter, transform, or build upon this work, you may distribute the resulting work only under the same or similar licence to this one.

- For any reuse or distribution, you must make clear to others the licence terms of this work.
- Any of the above conditions can be waived if you get permission from the copyright holder.
- The author's moral rights are retained in this licence.

[Disclaimer](#)

Your fair dealing and other rights are in no way affected by the above.  
 This is a human-readable summary of the Legal Code (the full licence) available in the following languages:  
[English](#) [French](#)



[Learn how to distribute your work using this licence](#)

# HT-Seq

Emma Bell, Felicia Gomez, Obi Griffith, Malachi Griffith, Huiming Xia

RNA-Seq Analysis

Sep 8<sup>th</sup>-10<sup>th</sup>, 2021



# Alternatives to FPKM

- Raw read counts for differential expression analysis
  - Assign reads/fragments to defined genes/transcripts, get “raw counts”
    - Transcript structures could still be defined by something like cufflinks

- HTSeq (htseq-count)

- <http://www-huber.embl.de/users/anders/HTSeq/doc/count.html>

```
htseq-count --mode intersection-strict --stranded no --minqual 1 --type  
exon --idattr transcript_id accepted_hits.sam chr22.gff >  
transcript_read_counts_table.tsv
```

- Caveats of ‘transcript’ analysis by htseq-count:

- Designed for genes - ambiguous reads from overlapping transcripts may not be handled!
- <http://seqanswers.com/forums/showthread.php?t=18068>

# HTSeq-count basically counts reads supporting a feature (exon, gene) by assessing overlapping coordinates

	union	intersection_strict	intersection_nonempty
	gene_A	gene_A	gene_A
	gene_A	no_feature	gene_A
	gene_A	no_feature	gene_A
	gene_A	gene_A	gene_A
	gene_A	gene_A	gene_A
	ambiguous	gene_A	gene_A
	ambiguous	ambiguous	ambiguous

Whether a read is counted depends on the nature of overlap and “mode” selected

# We are on a Coffee Break & Networking Session

Workshop Sponsors:



Canadian Centre for  
Computational  
Genomics



neuro

Institut-Hôpital  
neurologique de Montréal  
Montreal Neurological  
Institute-Hospital



OICR

Ontario Institute  
for Cancer Research

MiC:M McGill initiative in  
Computational Medicine



HPC4Health